


Swivel Joints

The Swivel Joint is designed to ensure free rotation of down hole tool string assemblies even when the tool string is held in significant tension.

The heavy duty versions are also capable of withstanding high impact forces suitable for use with the latest generation of high impact jars. By preventing the build up of torque in the tool string the chances of damage being caused to the wireline/well service strand are significantly reduced.

 By preventing the build up of torque in the tool string the chances of damage being caused to the wireline/well service strand are significantly reduced.

SWIVEL JOINT (BALL TYPE)			
Nominal Size	Fishing Neck	Connection Thread	Part Number
1.500"	1.375"	15/16-10	045SJT150000
1.875"	1.750"	1 1/16-10	045SJT187500
2.125"	1.750"	1 1/16-10	045SJT212500
2.500"	2.313"	1 9/16-10	045SJT250000
1.500"	1.375"	1-1/2 Halliburton HQC	045SJT150000HQC
1.875"	1.750"	1-7/8 Halliburton HQC	045SJT187500HQC
2.125"	1.750"	1-7/8 Halliburton HQC	045SJT212500HQC
2.500"	2.313"	2-1/2 Halliburton HQC	045SJT250000HQC

SWIVEL JOINT (HEAVY DUTY & BEARING VERSION)			
Nominal Size	Fishing Neck	Connection Thread	Part Number
1.500"	1.375"	15/16-10	151-1500-009
1.875"	1.750"	1 1/16-10	151-1875-008
2.125"	1.750"	1 1/16-10	151-2125-001
2.500"	2.313"	1 9/16-10	151-2500-001
2.500"	1.750"	1 1/16-10	151-2500-004
1.500"	1.375"	1-1/2 Petroline QLS	QLS-151-1500-001-1-1
1.875"	1.750"	1-7/8 Petroline QLS	QLS-151-1875-001-2-2
2.125"	1.750"	2-1//8 Petroline QLS	QLS-151-2125-001-2-2
2.500"	2.313"	2-1//2 Petroline QLS	QLS-151-2500-001-3-3



Wireline Operations - Slickline Tools

